

PVDF rod - extruded natural

Thickness (mm)	Tolerance (mm)		kg/m	£/m
	(min)	(max)		
10	+0.1	+0.5	0.15	15.47
12	+0.2	+0.7	0.22	22.68
15	+0.2	+0.7	0.32	32.99
20	+0.2	+0.7	0.59	53.10
25	+0.2	+0.9	0.92	82.80
30	+0.2	+0.9	1.32	118.80
35	+0.2	+1.1	1.80	162.00
40	+0.2	+1.1	2.34	210.60
50	+0.3	+1.3	3.69	332.10
60	+0.3	+1.6	5.27	474.30
70	+0.3	+1.6	7.15	643.50
80	+0.4	+2.0	9.22	829.80
90	+0.5	+2.2	11.72	1054.80
100	+0.6	+2.5	14.58	1312.20
110	+0.7	+3.0	17.60	1584.00
125	+0.8	+3.5	22.60	2034.00
140	+0.9	+3.8	28.50	2565.00
150	+1.0	+4.2	32.60	2934.00
180	+1.2	+5.0	46.87	4218.30
200	+1.3	+5.5	58.70	5283.00
250	+1.5	+6.2	90.20	9299.98
300	+1.5	+8.0	125.82	12972.05
350	+1.5	+11.0	171.26	17656.91
400	+1.5	+15.0	223.68	23061.41
500	+1.5	+20.0	349.50	36033.45

- Standard lengths: 1000, 2000mm
- All items priced in bold are normally ex-stock
- Items priced in grey, availability normally within 7-10 days