

PPC leather grain sheet - extruded black

Thickness (mm)	Tolerance (mm)		2440 x 1220mm		3000 x 1500mm	
	(min)	(max)	kg/ea	£/ea	kg/ea	£/ea
3	-0.20	+0.20	8.14	93.01	12.29	140.43
4.5	-0.21	+0.21	12.21	139.52	18.44	210.71
6	-0.26	+0.26	16.28	186.02	24.59	280.98
9	-0.35	+0.35	24.42	279.05	36.88	421.42
12	-0.44	+0.44	32.56	372.06	49.17	561.86

• All items priced in bold are normally ex-stock

PPC pinseal sheet - extruded beige (RAL 7032)

Thickness (mm)	Tolerance (mm)		2440 x 1220mm		3000 x 1500mm	
	(min)	(max)	kg/ea	£/ea	kg/ea	£/ea
3	-0.20	+0.20	8.14	96.81	12.29	146.17
4.5	-0.21	+0.21	12.21	145.21	18.44	219.31
6	-0.26	+0.26	16.28	193.63	24.59	292.46
9	-0.35	+0.35	24.42	290.43	36.88	438.63

• All items priced in bold are normally ex-stock

• All items priced in grey, availability on application, minimum quantity may apply

PPC weld rod - extruded natural / beige (RAL 7032) / black / grey / white

Spools (3kg)	£/kg	Spools (3kg)	£/kg
● 3mm	17.28	▲ 5.7mm	17.28
● 4mm	17.28	● 5.2mm	17.28

• All items priced in bold are normally ex-stock

PPC weld rod - extruded natural / beige (RAL 7032)

Coils (2-4kg)*	£/kg	Coils (2-4kg)	£/kg
● 3mm	17.28	▲ 6 x 3.6mm	17.28
● 4mm	17.28	● 5 x 3.5mm	17.28

• All items priced in bold are normally ex-stock

*Coil weights vary between 2kg and 4kg per pack