

PPS (fire retardant) sheet - extruded

grey (RAL 7037) (PE Protection 1-side)

Thickness (mm)	Tolerance (mm)		2440 x 1220mm		3000 x 1500mm		4000 x 2000mm	
	(min)	(max)	kg/ea	£/ea	kg/ea	£/ea	kg/ea	£/ea
3	-0.20	+0.20	8.14	112.82	12.29	209.83	22.08	336.63
4	-0.20	+0.20	10.85	150.38	16.39	279.82	29.44	448.84
4.5	-0.21	+0.21	12.21	169.24	-	-	-	-
6	-0.26	+0.26	16.28	225.64	24.59	419.82	44.16	673.27
8	-0.32	+0.32	-	-	32.76	559.31	58.88	897.69
9	-0.35	+0.35	24.42	338.46	36.87	629.49	-	-
10	-0.38	+0.38	-	-	41.40	706.82	73.60	1122.11
12	-0.44	+0.44	-	-	49.17	839.49	88.32	1346.52
15	-0.53	+0.53	-	-	62.10	1060.24	110.40	1683.16
20	-0.68	+0.68	-	-	82.80	1413.66	147.20	2244.21

- All items priced in bold are normally ex-stock
- All items priced in grey, availability normally within 7-10 days

PPS (fire retardant) weld rod - extruded

grey (RAL 7037) (PE Protection 1-side)

Coils 2kg	£/kg
● 3mm	18.55
● 4mm	18.55

- All items priced in bold are normally ex-stock
- All items priced in grey, availability normally within 7-10 days