

PPH rod - extruded

natural / beige (RAL 7032)

Diameter (mm)	Tolerance (mm)		kg/m	£/m	Diameter (mm)	Tolerance (mm)		kg/m	£/m
	(min)	(max)				(min)	(max)		
8	+0.1	+0.5	0.06	1.10	110	+0.7	+4.2	9.21	145.86
10	+0.1	+0.6	0.08	1.46	120	+0.8	+4.6	10.91	172.78
12	+0.2	+0.7	0.12	2.19	125	+0.8	+4.6	11.90	188.46
15	+0.2	+0.8	0.18	3.29	130	+0.8	+4.6	12.75	201.93
20	+0.2	+1.0	0.32	5.07	140	+0.9	+5.4	14.94	236.60
25	+0.2	+1.1	0.49	7.76	150	+1.0	+5.8	17.14	271.44
30	+0.2	+1.2	0.70	11.09	160	+1.1	+6.3	19.50	308.82
35	+0.2	+1.3	0.95	15.05	165	+1.1	+6.3	20.33	292.75
40	+0.2	+1.5	1.23	19.48	180	+1.2	+7.4	24.66	390.55
45	+0.3	+1.7	1.56	24.71	200	+1.3	+8.5	30.90	489.37
50	+0.3	+2.0	1.93	30.56	225	+1.3	+8.5	38.40	634.02
55	+0.3	+2.0	2.30	36.43	250	+1.3	+9.0	47.90	790.88
60	+0.3	+2.3	2.77	43.87	280	+1.3	+9.5	58.20	960.94
65	+0.3	+2.3	3.27	51.79	300	+1.3	+10.0	68.70	1134.31
70	+0.3	+2.5	3.75	59.39	350	+1.3	+12.0	93.00	1535.53
75	+0.3	+2.5	4.23	66.99	400	+1.3	+12.0	122.70	2250.54
80	+0.4	+3.0	4.88	77.29	500	+1.3	+12.0	189.00	5116.06
90	+0.5	+3.4	6.18	97.88	600	+1.3	+20.0	270.50	15498.151
100	+0.6	+3.8	7.62	120.68	700	+1.3	+20.0	365.70	20952.58

- Standard lengths: 1000, 2000mm
- All items priced in bold are normally ex-stock
- Items priced in grey, availability normally within 7-10 days
- Black available on request at above prices +10%

PPH hollow rod - extruded

beige (RAL 7032)

Size (mm) O/D x I/D	kg/m	£/m	Size (mm) O/D x I/D	kg/m	£/m
30 x 15	0.51	13.88	90 x 50	4.21	114.58
40 x 15	1.07	29.12	100 x 70	3.98	108.32
50 x 20	1.58	43.00	120 x 50	9.15	249.01
50 x 30	1.21	32.93	140 x 70	11.45	311.61
60 x 30	2.03	55.25	170 x 120	11.21	305.08
70 x 30	3.01	81.91	200 x 120	20.64	561.72
80 x 40	3.61	98.25	-	-	-

- Standard lengths: 1000, 2000mm
- Tolerances: O.D +5%, I.D. -10%
- Items priced in grey, availability normally within 7-10 days