

## PET sheet - extruded natural

Thickness (mm)	Tolerance (mm)		1000mm Wide	
	(min)	(max)	kg/m	£/m
2	-0.15	+0.15	2.88	69.79
3	-0.20	+0.20	4.32	104.69
4	-0.20	+0.20	5.76	139.57
5	-0.25	+0.25	7.20	174.47
6	-0.25	+0.25	8.64	209.36
8	+0.20	+0.90	12.62	305.80

- Standard lengths: 2-3mm - 2000mm, 4-8mm - 1000, 2000mm
- All items priced in bold are normally ex-stock
- Items priced in grey, availability normally within 7-10 days

## PET sheet - extruded natural

Thickness (mm)	Tolerance (mm)		610mm Wide	
	(min)	(max)	kg/m	£/m
10	+0.3	+1.5	9.71	157.84
12	+0.3	+1.5	11.50	186.94
15	+0.3	+1.5	14.17	230.35
20	+0.3	+1.5	18.63	302.85
25	+0.3	+1.5	23.08	375.19
30	+0.5	+2.5	28.07	456.31
40	+0.5	+2.5	36.98	601.16
50	+0.5	+2.5	45.89	746.00
60	+0.5	+3.5	55.24	897.99
80	+0.5	+5.0	73.73	1198.56
100	+0.5	+5.0	91.55	1488.25

- Standard lengths: 1000, 2000, 3000mm
- Black available on application
- All items priced in bold are normally ex-stock
- All items priced in grey, availability on application, minimum quantity may apply

## PET ZX sheet - extruded light grey - available on request (PET ZX contains a solid lubricant additive)