

# PET rod - extruded

## natural / black

Diameter (mm)	Tolerance (mm)		kg/m	Natural	Black
	(min)	(max)		£/m	£/m
12	+0.2	+0.7	0.18	3.23	-
16	+0.2	+0.7	0.31	5.58	5.75
20	+0.2	+0.7	0.47	7.64	7.88
25	+0.2	+0.9	0.74	12.03	12.40
30	+0.2	+0.9	1.06	17.27	17.78
36	+0.2	+1.1	1.52	24.71	-
40	+0.2	+1.1	1.87	30.40	31.35
45	+0.2	+1.3	2.38	38.69	-
50	+0.3	+1.3	2.92	47.47	48.95
55	+0.3	+1.3	3.52	57.22	-
60	+0.3	+1.6	4.20	68.27	70.42
65	+0.3	+1.6	4.92	79.98	-
70	+0.3	+1.6	5.69	92.50	95.40
80	+0.4	+2.0	7.46	121.27	125.07
90	+0.5	+2.2	9.42	153.14	-
100	+0.6	+2.5	11.65	189.38	195.32
110	+0.7	+3.0	14.15	230.02	-
120	+0.8	+3.5	16.91	274.89	-
130	+0.9	+3.8	19.76	321.22	-
140	+0.9	+3.8	22.93	372.75	-
150	+1.0	+4.2	26.23	426.40	-
180	+1.2	+5.0	37.94	581.85	-
200	+1.3	+5.5	46.81	760.95	-

- Standard lengths: 1000, 3000mm
- All items priced in bold are normally ex-stock
- Items priced in grey, availability normally within 7-10 days

# PET ZX rod - extruded

## light grey

Thickness (mm)	Tolerance (mm)		kg/m	£/m
	(min)	(max)		
20	+0.2	+0.7	0.49	22.68
25	+0.2	+0.9	0.76	35.18
30	+0.2	+0.9	1.08	49.99
40	+0.2	+1.1	1.91	88.41
50	+0.3	+1.3	2.98	137.94
60	+0.3	+1.6	4.28	198.11
70	+0.3	+1.6	5.81	268.93
80	+0.4	+2.0	7.60	351.79
100	+0.6	+2.5	11.90	550.83

- Standard lengths: 1000, 3000mm
- PET ZX contains a solid lubricant additive
- Items priced in grey, availability normally within 7-10 days