

# U-PVC ext. hexagonal bar / grey (RAL 7011)



U-PVC extruded hexagonal bar is stocked in grey as standard (ivory on application) assisting in the manufacture of fixing parts such as nuts and bolts.

Size (across flats; mm)	kg/m	£/m	Size (across flats; mm)	kg/m	£/m
10	0.13	1.59	22	0.62	7.60
12	0.20	2.45	25	0.78	9.56
14	0.24	2.94	28	1.00	12.26
17	0.36	4.41	32	1.30	15.94
19	0.45	5.52	36	1.58	19.37

Standard lengths: 2000mm  
Ivory on application

# U-PVC ext. angle / grey (RAL 7011)



U-PVC extruded angle is stocked in grey as standard (ivory on application). Used in many applications, however invaluable as strengtheners in the manufacture of tanks.

Size W x H x T (mm)	kg/m	£/m	Size W x H x T (mm)	kg/m	£/m
15 x 15 x 1.9	0.08	1.19	40 x 40 x 5	0.55	8.16
20 x 20 x 4	0.21	3.11	50 x 50 x 6	0.83	12.31
25 x 25 x 3	0.22	3.26	60 x 60 x 7	1.14	16.91
30 x 30 x 5	0.40	5.93	70 x 70 x 7	1.30	19.28

Standard lengths: 5000mm  
Ivory on application  
W: width. H: height. T: thickness

# U-PVC ext. channel / grey (RAL 7011)



U-PVC extruded channel is stocked in grey as standard (ivory on application). This profile assists in applications such as covering corrosive strengtheners.

Size W x H x T (mm)	kg/m	£/m	Size W x H x T (mm)	kg/m	£/m
14 x 40 x 4	0.48	7.12	50 x 25 x 5	0.62	9.19
20 x 20 x 7	0.44	6.53	60 x 20 x 4	0.57	8.45
40 x 40 x 3	0.50	7.42	70 x 35 x 5	0.94	13.94
48 x 44 x 3	0.60	8.90	-	-	-

All products are ex-stock unless in grey, availability on application  
Standard lengths: 5000mm  
Ivory on application  
W: width. H: height. T: thickness