

PE300 rod - extruded natural / black

Diameter (mm)	Tolerance (mm)		kg/m	Avail'	Diameter (mm)	Tolerance (mm)		kg/m	Avail'
	(min)	(max)				(min)	(max)		
10	+0.1	+0.6	0.08	✓	110	+0.7	+4.2	9.61	✓
12	+0.2	+0.7	0.12	✓	120	+0.8	+4.6	11.38	✓
15	+0.2	+0.8	0.19	✓	125	+0.8	+4.6	12.42	✓
20	+0.2	+1.0	0.33	✓	130	+0.8	+4.6	13.32	✓
25	+0.2	+1.1	0.51	✓	140	+0.9	+5.4	15.58	✓
30	+0.2	+1.2	0.72	✓	150	+1.0	+5.8	17.90	✓
35	+0.2	+1.3	0.99	✓	160	+1.1	+6.3	20.35	✓
40	+0.2	+1.5	1.28	✓	180	+1.2	+7.4	25.70	✓
45	+0.3	+1.7	1.62	✓	200	+1.3	+8.5	32.20	✓
50	+0.3	+2.0	2.02	✓	225	+1.3	+8.5	42.00	✓
55	+0.3	+2.0	2.36	✓	250	+1.3	+9.0	50.00	✓
60	+0.3	+2.3	2.88	✓	280	+1.3	+9.5	60.75	○
65	+0.3	+2.3	3.37	✓	300	+1.3	+10.0	71.80	✓
70	+0.3	+2.5	3.91	✓	350	+1.3	+12.0	98.00	✓
75	+0.3	+2.5	4.50	✓	400	+1.3	+12.0	127.00	○
80	+0.4	+3.0	5.10	✓	500	+1.3	+12.0	197.00	○
90	+0.5	+3.4	6.45	✓	600	+1.3	+20.0	290.00	○
100	+0.6	+3.8	7.96	✓	700	+1.3	+20.0	395.00	○

- Standard lengths: 1000, 2000mm
- ✓ – Items are normally ex-stock
- – Items availability normally within 7-10 days

PE300 hollow rod - extruded black

Size (mm) O/D x I/D	kg/m	Availability	Size (mm) O/D x I/D	kg/m	Availability
30 x 15	0.54	○	90 x 50	4.44	○
50 x 30	1.27	○	100 x 70	4.25	○
70 x 30	3.20	○	140 x 70	12.07	○
75 x 40	3.19	○	200 x 120	21.38	○
80 x 40	3.81	○	-	-	-

- Standard lengths: 1000, 2000mm
- Tolerances: O.D +5%, I.D. -10%
- – Items availability normally within 7-10 days