

# PE9000GF sheet - pressed and planed lime green

Thickness (mm)	Tolerance (mm)		kg/ea	2000 x 1000mm	Availability
	(min)	(max)			
10	-0.2	+0.2	19.80		✓
12	-0.2	+0.2	23.80		○
15	-0.2	+0.2	29.70		✓
20	-0.2	+0.2	39.60		✓
25	-0.2	+0.2	49.50		✓
30	-0.2	+0.2	59.40		✓
35	-0.3	+0.3	69.30		○
40	-0.3	+0.3	79.20		✓
50	-0.3	+0.3	99.00		✓
60	-0.3	+0.3	118.80		○
70	-0.3	+0.3	138.60		○
80	-0.3	+0.3	158.40		○

- All thicknesses and grades also available in 3000x1000 - availability on application
- Thicknesses upto 150mm available on application
- ✓ – Items are normally availability within 5-7 days
- – Items availability on application

# PE9000 AST (anti-static) sheet - pressed and planed black

Thickness (mm)	Tolerance (mm)		kg/ea	2000mm x 1000mm	Availability
	(min)	(max)			
5	-0.3	+0.3	9.80		○
6	-0.3	+0.3	11.76		○
8	-0.2	+0.2	15.70		○
10	-0.2	+0.2	19.60		✓
12	-0.2	+0.2	23.60		○
15	-0.2	+0.2	29.40		✓
20	-0.2	+0.2	39.20		✓
25	-0.2	+0.2	49.00		✓
30	-0.2	+0.2	58.80		✓
35	-0.3	+0.3	68.60		○
40	-0.3	+0.3	78.40		✓
50	-0.3	+0.3	98.00		✓
60	-0.3	+0.3	117.60		○
70	-0.3	+0.3	137.20		○
80	-0.3	+0.3	156.80		○

- All thicknesses and grades also available in 3000x1000 - availability on application
- Thicknesses upto 150mm available on application
- ✓ – Items are normally availability within 5-7 days
- – Items availability on application