

PET Rod

PET rod | extruded

Natural | Black



Diameter (mm)	Tolerance (mm)	kg / m	1000mm length	
			Natural	Black
12	(+0.20 / +0.70)	0.17	○	○
16	(+0.20 / +0.70)	0.30	✓	✓
20	(+0.20 / +0.70)	0.47	✓	✓
25	(+0.20 / +0.90)	0.73	✓	✓
30	(+0.20 / +0.90)	1.04	✓	✓
36	(+0.20 / +1.10)	1.50	✓	○
40	(+0.20 / +1.10)	1.84	✓	✓
45	(+0.20 / +1.30)	2.34	✓	○
50	(+0.30 / +1.30)	2.88	✓	✓
56	(+0.30 / +1.30)	3.60	●	○
60	(+0.30 / +1.60)	4.15	✓	✓
65	(+0.30 / +1.60)	4.85	✓	○
70	(+0.30 / +1.60)	5.62	✓	✓
80	(+0.40 / +2.00)	7.36	✓	●
90	(+0.50 / +2.20)	9.31	✓	○
100	(+0.60 / +2.50)	11.50	✓	○
110	(+0.70 / +3.00)	13.95	●	○
120	(+0.80 / +3.50)	16.65	✓	○
130	(+0.90 / +3.80)	19.55	✓	○
140	(+0.90 / +3.80)	22.60	○	○
150	(+1.00 / +4.20)	26.00	✓	○
160	(+1.10 / +4.50)	29.60	✓	-
180	(+1.20 / +5.00)	37.40	●	○
200	(+1.30 / +5.50)	46.15	✓	○

Standard lengths: 3000 and 1000mm.

Colours shown for illustration purposes only.

- ✓ Items are normally stocked.
- Items available on application, minimum quantity may apply.
- Items available on application, normally within 7 days.