

PET Rod

PET ZX rod | extruded

Light grey ●



Diameter (mm)	Tolerance (mm)	kg / m	Light grey
10	(+0.10 / +0.70)	0.12	○
12	(+0.20 / +0.80)	0.18	○
15	(+0.20 / +0.80)	0.28	○
16	(+0.20 / +0.80)	0.31	○
18	(+0.20 / +0.80)	0.40	○
20	(+0.20 / +0.80)	0.49	✓
22	(+0.20 / +1.00)	0.59	○
25	(+0.20 / +1.00)	0.75	✓
28	(+0.20 / +1.00)	0.94	○
30	(+0.20 / +1.00)	1.08	✓
32	(+0.20 / +1.20)	1.24	○
36	(+0.20 / +1.20)	1.56	○
40	(+0.20 / +1.20)	1.91	✓
45	(+0.30 / +1.30)	2.42	○
50	(+0.30 / +1.30)	2.98	✓
56	(+0.30 / +1.30)	3.73	○
60	(+0.30 / +1.60)	4.29	✓

Diameter (mm)	Tolerance (mm)	kg / m	Light grey
65	(+0.30 / +1.60)	5.02	○
70	(+0.30 / +1.60)	5.82	✓
75	(+0.40 / +2.00)	6.71	○
80	(+0.40 / +2.00)	7.62	✓
85	(+0.50 / +2.20)	8.62	○
90	(+0.50 / +2.20)	9.64	✓
95	(+0.60 / +2.50)	10.78	○
100	(+0.60 / +2.50)	11.92	✓
110	(+0.70 / +3.00)	14.46	○
120	(+0.80 / +3.50)	17.25	●
125	(+0.80 / +3.50)	18.69	○
130	(+0.90 / +3.80)	20.25	○
140	(+0.90 / +3.80)	23.42	○
150	(+1.00 / +4.20)	26.92	●
170	(+1.20 / +5.00)	34.64	○
180	(+1.20 / +5.00)	38.75	○
200	(+1.30 / +5.50)	47.82	●

Standard lengths: 3000 and 1000mm.
PET ZX contains a solid lubricant additive.

Colours shown for illustration purposes only.

- ✓ Items are normally stocked.
- Items available on application, normally within 7 days.
- Items available on application, minimum quantity may apply.