

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)

Premierbond HT - DoP _[EN] _ 002 _ No C52324822-1969

CE 1213
17 For essential characteristics see DoP on our website www.cladright.co.uk DoP nr. C52324822-1969
EN 15651.1 F-EXT-INT-CC EN 15651.3 S EN 15651.4 PW-EXT-INT-CC

1. Unique identification code of product-type: Premierbond HT - Hybrid MS polymer technology
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4): Batch number: See product packaging
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Sealants for façade elements Sealants for sanitary joints Sealants for pedestrian walkways
EN 15651.1: F-EXT-INT-CC (CLASS 25HM)
EN 15651.3: S (CLASS XS3)
EN 15651.4: PW-EXT-INT-CC (CLASS 25HM)
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5): Cladright™, 68 SCUDAMORE ROAD, BRAUNSTONE FIRTH IND. EST. LEICESTER, LE3 1UA
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): Not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
System 3 for reaction to fire
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:
The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-3 / EN 15651-4 and reaction to fire under system 3 and issued a test report.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not relevant



DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)

Premierbond HT - DoP _[EN]_ 002 _ No C52324822-1969

9. Declared performance - Conditioning substrate:

Procedure B (according to ISO 8340)

Mortar M1 (with primer P03)

Glass (without primer)

Anodised aluminium (without primer)



Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

Substrate:

Glass (without primer)

Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness:		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 20 %	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	3	
Durability	Pass	


DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)

Premierbond HT - DoP _ [EN] _ 002 _ No C52324822-1969

Substrate:

Mortar M1 (with primer P03)



1213

17
 For essential characteristics
 see DoP on our website
www.cladright.co.uk
 DoP nr. C52324822-1969

EN 15651.1
 F-EXT-INT-CC
EN 15651.3
 S
EN 15651.4
 PW-EXT-INT-CC

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-4:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness:		
Tensile properties at maintained extension	NF	
Loss of volume	≤ 10 %	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus: ≤ 50 %	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

(*) See material safety data sheet NPD: No Performance Determined NF:

No Failure

NR: Not required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Cladright™