



U-PVC rod - extruded grey (RAL 7011)

C-PVC rod - extruded light grey (RAL 9310)

Dia. (mm)	Tolerance (mm)		U-PVC		C-PVC		Dia. (mm)	Tolerance (mm)		U-PVC		C-PVC	
	(min)	(max)	kg/m	Avail'	kg/m	Avail'		(min)	(max)	kg/m	Avail'	kg/m	Avail'
5	+0.1	+0.4	0.03	○	-	-	75	+0.3	+2.5	6.48	✓	-	-
6	+0.1	+0.4	0.04	○	-	-	80	+0.4	+2.5	7.30	✓	8.32	○
8	+0.1	+0.5	0.08	✓	-	-	85	+0.4	+2.5	8.06	○	-	-
10	+0.1	+0.6	0.12	○	0.14	○	90	+0.5	+2.8	9.24	✓	10.53	○
12	+0.2	+0.7	0.17	✓	-	-	100	+0.6	+3.0	11.39	✓	12.98	○
15	+0.2	+0.8	0.26	✓	0.31	○	110	+0.7	+3.0	13.76	✓	15.23	○
18	+0.2	+0.9	0.38	○	-	-	120	+0.8	+3.5	16.39	✓	-	-
20	+0.2	+1.0	0.47	✓	0.54	○	125	+0.8	+3.5	17.79	○	19.76	○
22	+0.2	+1.1	0.53	○	-	-	130	+0.8	+4.0	19.26	○	-	-
25	+0.2	+1.1	0.72	✓	0.83	○	140	+0.9	+4.0	22.31	○	-	-
28	+0.2	+1.2	0.89	○	-	-	150	+1	+4.2	25.63	○	32.25	○
30	+0.2	+1.2	1.04	✓	1.19	○	160	+1.1	+4.5	28.30	○	-	-
32	+0.2	+1.3	1.16	✓	-	-	180	+1.2	+8.0	38.00	○	-	-
35	+0.2	+1.3	1.35	✓	-	-	200	+1.3	+8.0	47.30	○	-	-
40	+0.2	+1.5	1.84	✓	2.11	○	225*	+1.3	+8.0	59.90	○	-	-
45	+0.3	+1.7	2.33	✓	-	-	250*	+1.5	+8.0	71.30	○	-	-
50	+0.3	+2.0	2.88	✓	3.30	○	280*	+1.5	+8.0	92.00	○	-	-
55	+0.3	+2.0	3.44	✓	-	-	300*	+1.5	+10.0	106.00	○	-	-
60	+0.3	+2.3	4.14	✓	4.74	○	350*	+1.5	+15.0	142.00	○	-	-
65	+0.3	+2.3	4.71	○	-	-	400*	+1.5	+20.0	185.00	○	-	-
70	+0.3	+2.5	5.61	✓	6.39	○	-	-	-	-	-	-	

- Standard lengths: 1000, 2000mm. *225 - 400mm dia. 500mm lengths
- ✓ – Items are normally ex-stock
- – Items availability normally within 7-10 days
- – Items not available
- U-PVC rod also available in black and red, on application