

Nylon 6 rod - extruded

natural / black

Diameter (mm)	Tolerance (mm)		kg/m	Natural Availability	Black Availability
	(min)	(max)			
5	+0.1	+0.4	0.03	✓	-
6	+0.1	+0.4	0.04	✓	-
8	+0.1	+0.5	0.07	✓	-
10	+0.1	+0.5	0.10	✓	○
12	+0.2	+0.7	0.14	✓	-
15	+0.2	+0.7	0.22	✓	○
20	+0.2	+0.7	0.38	✓	✓
22	+0.2	+0.9	0.46	○	-
25	+0.2	+0.9	0.60	✓	✓
28	+0.2	+0.9	0.75	○	-
30	+0.2	+0.9	0.85	✓	✓
32	+0.2	+1.1	0.97	✓	○
36	+0.2	+1.1	1.22	✓	✓
40	+0.2	+1.1	1.50	✓	✓
45	+0.3	+1.3	1.91	✓	○
50	+0.3	+1.3	2.35	✓	✓
56	+0.3	+1.3	2.93	✓	○
60	+0.3	+1.6	3.38	✓	✓
65	+0.3	+1.6	3.95	✓	-
70	+0.3	+1.6	4.64	✓	✓
75	+0.4	+2.0	5.30	✓	-
80	+0.4	+2.0	6.05	✓	✓
90	+0.5	+2.2	7.67	✓	✓
100	+0.6	+2.5	9.45	✓	✓
110	+0.7	+3.0	11.50	✓	-
120	+0.8	+3.5	13.70	✓	✓
130	+0.9	+3.8	16.10	○	-
140	+0.9	+3.8	18.70	○	-
150	+1.0	+4.2	21.40	✓	○
165	+1.2	+5.0	25.68	○	-
180	+1.2	+5.0	30.47	○	-
200	+1.2	+5.5	37.60	○	-

• Standard lengths: 1000, 2000, 3000mm

✓ – Items are normally ex-stock

○ – Items availability on application, minimum quantity may apply

- – Items not available