

PE1000 rod - ram extruded

natural / black

Diameter (mm)	Tolerance (mm)		kg/m	Natural Availability	Black Availability
	(min)	(max)			
10*	+0.1	+0.6	0.09	○	○
12*	+0.2	+0.7	0.13	○	○
15*	+0.2	+0.8	0.19	○	○
20	+0.2	+1.0	0.33	✓	✓
25	+0.2	+1.1	0.55	✓	✓
30	+0.2	+1.2	0.75	✓	✓
35	+0.2	+1.3	1.00	○	○
40	+0.2	+1.5	1.28	✓	✓
45	+0.3	+1.7	1.60	✓	✓
50	+0.3	+2.0	2.20	✓	✓
55	+0.3	+2.0	2.37	✓	○
60	+0.3	+2.3	2.92	✓	✓
70	+0.3	+2.5	3.80	✓	✓
80	+0.4	+3.0	5.10	✓	✓
90	+0.5	+3.4	6.40	✓	✓
100	+0.6	+3.8	8.00	✓	✓
110	+0.7	+4.2	9.30	✓	✓
125	+0.8	+4.6	12.20	✓	✓
130	+0.8	+4.6	13.40	✓	✓
140	+0.9	+5.4	15.50	✓	✓
150	+1.0	+5.8	17.90	✓	✓
160	+1.1	+6.3	19.80	✓	✓
180	+1.2	+7.4	27.00	✓	✓
200	+1.3	+8.5	33.20	✓	✓

- Standard lengths: 1000, 2000mm
- Green available on application
- ✓ – Items are normally ex-stock
- – Items availability normally within 7-10 days
- * 10 to 15mm dia may be turned down from 20mm bar