

PETP rod - extruded

natural / black

Diameter (mm)	Tolerance (mm)		kg/m	Natural Availability	Black Availability
	(min)	(max)			
12	+0.2	+0.7	0.18	✓	-
16	+0.2	+0.7	0.31	✓	✓
20	+0.2	+0.7	0.47	✓	✓
25	+0.2	+0.9	0.74	✓	✓
30	+0.2	+0.9	1.06	✓	✓
36	+0.2	+1.1	1.52	✓	-
40	+0.2	+1.1	1.87	✓	✓
45	+0.2	+1.3	2.38	✓	-
50	+0.3	+1.3	2.92	✓	✓
56	+0.3	+1.3	3.57	✓	-
60	+0.3	+1.6	4.20	✓	✓
65	+0.3	+1.6	4.92	✓	-
70	+0.3	+1.6	5.69	✓	✓
80	+0.4	+2.0	7.46	✓	○
90	+0.5	+2.2	9.42	✓	-
100	+0.6	+2.5	11.65	✓	○
110	+0.7	+3.0	14.15	✓	-
120	+0.8	+3.5	16.91	✓	-
130	+0.9	+3.8	19.76	✓	-
140	+0.9	+3.8	22.93	✓	-
150	+1.0	+4.2	26.23	✓	-
180	+1.2	+5.0	37.94	✓	-
200	+1.3	+5.5	46.81	✓	-

• Standard lengths: 1000, 3000mm

✓ – Items in are normally ex-stock

○ – Items availability normally within 7-10 days

- – Items not available

PETP ZX rod - extruded

light grey

Thickness (mm)	Tolerance (mm)		kg/m	Availability
	(min)	(max)		
20	+0.2	+0.7	0.49	✓
25	+0.2	+0.9	0.76	✓
30	+0.2	+0.9	1.08	✓
40	+0.2	+1.1	1.91	✓
50	+0.3	+1.3	2.98	✓
60	+0.3	+1.6	4.28	✓
70	+0.3	+1.6	5.81	✓
80	+0.4	+2.0	7.60	✓
90	+0.5	+2.2	9.61	✓
100	+0.6	+2.5	11.90	✓

• Standard lengths: 1000, 3000mm

• PET ZX contains a solid lubricant additive

✓ - All items are normally ex-stock