

PETP sheet - extruded natural

Thickness (mm)	Tolerance (mm)		kg/m	1000mm Wide	Availability
	(min)	(max)			
2	-0.15	+0.15	2.88		○
3	-0.20	+0.20	4.32		○
4	-0.20	+0.20	5.76		○
5	-0.25	+0.25	7.20		○
6	-0.25	+0.25	8.64		○
8	+0.20	+0.90	12.62		○

• Standard lengths: 2-3mm - 2000mm, 4-8mm - 1000, 2000mm

✓ – Items are normally ex-stock

○ – Items availability normally within 7-10 days

PETP sheet - extruded natural / black

Thickness (mm)	Tolerance (mm)		kg/m	610mm Wide Natural Availability	Black Availability
	(min)	(max)			
10	+0.3	+1.5	9.71	✓	○
12	+0.3	+1.5	11.50	✓	-
15	+0.3	+1.5	14.17	✓	-
20	+0.3	+1.5	18.63	✓	○
25	+0.3	+1.5	23.08	✓	-
30	+0.5	+2.5	28.07	✓	○
40	+0.5	+2.5	36.98	✓	○
50	+0.5	+2.5	45.89	✓	-
60	+0.5	+3.5	55.24	○	○
80	+0.5	+5.0	73.73	○	○
100	+0.5	+5.0	91.55	○	-

• Standard lengths: 1000, 2000, 3000mm

• Black available on application

✓ – Items are normally ex-stock

○ – Items availability on application, minimum quantity may apply

- – Items not available

PETP ZX sheet - extruded light grey - available on request

(PET ZX contains a solid lubricant additive)