

PPH rod - extruded

natural / beige (RAL 7032)

Diameter (mm)	Tolerance (mm)		kg/m	Availability	Diameter (mm)	Tolerance (mm)		kg/m	Availability
	(min)	(max)				(min)	(max)		
8	+0.1	+0.5	0.06	○	110	+0.7	+4.2	9.21	✓
10	+0.1	+0.6	0.08	✓	120	+0.8	+4.6	10.91	✓
12	+0.2	+0.7	0.12	✓	125	+0.8	+4.6	11.90	✓
15	+0.2	+0.8	0.18	✓	130	+0.8	+4.6	12.75	✓
20	+0.2	+1.0	0.32	✓	140	+0.9	+5.4	14.94	✓
25	+0.2	+1.1	0.49	✓	150	+1.0	+5.8	17.14	✓
30	+0.2	+1.2	0.70	✓	160	+1.1	+6.3	19.50	✓
35	+0.2	+1.3	0.95	✓	165	+1.1	+6.3	20.33	✓
40	+0.2	+1.5	1.23	✓	180	+1.2	+7.4	24.66	✓
45	+0.3	+1.7	1.56	✓	200	+1.3	+8.5	30.90	✓
50	+0.3	+2.0	1.93	✓	225	+1.3	+8.5	38.40	✓
55	+0.3	+2.0	2.30	✓	250	+1.3	+9.0	47.90	✓
60	+0.3	+2.3	2.77	✓	280	+1.3	+9.5	58.20	○
65	+0.3	+2.3	3.27	✓	300	+1.3	+10.0	68.70	✓
70	+0.3	+2.5	3.75	✓	350	+1.3	+12.0	93.00	✓
75	+0.3	+2.5	4.23	✓	400	+1.3	+12.0	122.70	○
80	+0.4	+3.0	4.88	✓	500	+1.3	+12.0	189.00	○
90	+0.5	+3.4	6.18	✓	600	+1.3	+20.0	270.50	○
100	+0.6	+3.8	7.62	✓	700	+1.3	+20.0	365.70	○

- Standard lengths: 1000, 2000mm
- ✓ – Items are normally ex-stock
- – Items availability normally within 7-10 days
- Black available on request

PPH hollow rod - extruded

beige (RAL 7032)

Size (mm) O/D x I/D	kg/m	Availability	Size (mm) O/D x I/D	kg/m	Availability
30 x 15	0.51	○	90 x 50	4.21	○
40 x 15	1.07	○	100 x 70	3.98	○
50 x 20	1.58	○	120 x 50	9.15	○
50 x 30	1.21	○	140 x 70	11.45	○
60 x 30	2.03	○	170 x 120	11.21	○
70 x 30	3.01	○	200 x 120	20.64	○
80 x 40	3.61	○	-	-	-

- Standard lengths: 1000, 2000mm
- Tolerances: O.D +5%, I.D. -10%
- – Items availability normally within 7-10 days